

Platform body - medium series



Product benefits

- Clamped/bolted subframe and cross members, hot-dip galvanised
- Aluminium hollow profile rear wall, 800 mm high, foldable, with 2 integrated folding supports
- External frame with 11 pairs of recessed lashing points for load securing
- Resin-coated plywood floor, 30 mm, for stacker axle loads up to 2.5 t
- OPTIONAL: Vertical liftgate with upper extending flap, for distribution transport
- OPTIONAL: Bolted portal frame at rear incl. full-length, fully opening double door

Product details

TYPE DESIGNATION

PLATFORM BODY - UP TO 14 T TOTAL WEIGHT

WEIGHTS

Body weight: approx. 1.2 t

DIMENSIONS

Internal platform length: approx. 6,100 mm
Internal platform width: approx. 2,480 mm
Total width: 2,550 mm

Load space internal height: approx. 2,000 - 2,300 mm

Load space internal height, body height, loading height, total height etc. can only be checked and announced upon specification of the exact truck data

FRAME

Clamped/bolted steel construction,
with attached cross members - design height approx. 210 mm
11 pairs of recessed lashing points according to UVV

FLOOR

Resin-coated birch plywood floor, 30 mm, flush with external frame
(floor load capacity up to 2.5 t stacker axle load)

PAINTWORK

Blasted with steel granulate, treated with zinc dust primer and spray painted
2-component acrylic paints for commercial vehicles (standard RAL or truck colour)

hot-dip galvanised - unpainted = subframe and cross members

Plastic and hot-dip galvanised parts unpainted,
powder-coated attachments black

Reflective contour marking strips across entire length of sides (continuing onto truck cab) and all-round contour marking at rear
(white on sides and red at rear by default), according to ECE 48

ACCESSORIES

Rear markings as per ECE standards

ATTACHMENTS

Rear crash guard
Side wall stop buffer
Bracket for wheel chock(s)

SIDE WALLS

Fixed aluminium hollow profile front wall, 1,700 mm, with 2 full-height centre supports

Front wall reinforced inside with 3/5 mm aluminium chequer plate, approx. 650 mm high

2-part aluminium hollow profile side walls, 600/25 mm,
with rubber seal and bracket recess for tarpaulin overhang (360 mm),
with French tarpaulin brackets, spacing approx. 400 mm (not customs-compliant),
foldable with latch-type tension locks 681-S1

Foldable aluminium hollow profile rear wall, 600 mm high, with rubber seal and bracket recess,
customs-compliant with tarpaulin brackets,
with latch-type tension locks 681-S1

Folding step

POSTS/COVER/TARPAULIN

2 front corner posts, bolted to front, 1,700 mm high

2 foldable centre posts, 1,800 mm high, split

2 rear corner posts, bolted to sides, 1,700 mm high

3 rows of softwood slot-in slats, 100/27 mm, in pockets, spacing: 400/2 x 200 mm

Fixed pole roof with 6 rows of longitudinal pipes, 60 mm, and transverse bows for posts.

Tarpaulin made from high-strength Trevira fabric with translucent roof, all-round rubber tensioner,
tarpaulin manufacturer as per factory specifications, tarpaulin colour according to availability

Product impressions





